



### ESSAE POS 815

A Wide Choice of Sleek & Elegant POS system to power your Business growth

#### Specification

##### System

Processor : **POS-815B** : Intel Baytrail J1900 QUAD CORE 2.00 GHz Embedded, 2 MB Cache memory

**POS-815C** : Intel Core i3-6100U 2.30 GHz , 3 MB Cache memory

System Memory : **POS-815B** : 4 GB DDR3L RAM (Expandable upto 8 GB )

**POS-815C** : 4 GB DDR4 RAM ( Expandable upto 16 GB )

Storage Device : 128 GB SSD or 500 GB HDD

Power Supply : DC 12V / 5A 60W

OS Support : Windows 10 IOT Enterprise; Windows Embedded POSReady 7; Linux

#### Display & Touch

LCD : 15" TFT LCD with LED Backlight, Anti-glare

Resolution : 1024 \* 768

Brightness : 350 nits

Touch : Projected Capacitive Touch ( PCAP )- True FLAT

#### Interface

Serial Port : (DB9) : 3

Standard USB Port : **POS-815B** : 5 , **POS-815C** : 4

LAN Port : **POS-815B** : 1 \* Gigabit LAN, **POS-815C** : 2 \* Gigabit LAN

Display Port : **POS-815CB** : 1 \* VGA , **POS-815C** : 1 \* HDMI

Factory Option : WiFi- LAN module ( Mini-Pcle)

Audio : 1 \* Line-in, 1 \* Line-out

#### Physical Dimension

Dimension [ W\*D\*H ] : 382 \* 256 \* 355 (mm)

Net Weight : 5.3 Kg

#### Environmental

Operating Condition : 5°C to 40°C

#### Optional Accessories

Printer : Thermal Printer. 79.5 mm paper, 220 mm/sec, Auto-cutter

Interface : USB only or Serial +USB+LAN(Factory option)

Cash Drawer : 5-Bill/8-Coin Metal Cash Drawer with Lock & Key and micro-switch

MSR : 3 Track-OPOS Compliant, USB interface

Customer Display : 10.4 Touch (PCAP) LCD USB interface (rear mounted) Display resolution: 800\*600

or 20\*2 Graphic LCD(rear mounted)

or 20\*2 Graphic LCD(pole type)

Wall Mount Kit : VESA-Compliant Wall Mounting Kit

#### Contact us



Source and Process Solutions,  
No. 1433, 2nd Floor, Pipeline Road,  
West of Chord Road, 2nd Stage,  
Mahalakshimpuram, Bangalore — 560086  
Karnataka, India



+91 080-41483787  
+91 6366 880 942/43/44/45



contact@sourceandprocess.in



www.sourceandprocess.in