



POSBANK Apexa Prime i5

Specification System

Processor : Inter Core i5-7200U (3M Cache, 3.10 GHz, 2 Cores)
System Memory : 4GB Standard, DDR4L 2133 MT/s, (Max. 16GB)
Storage Device : SATA 3 (6Gb/s) 2.5 inch SSD 128GB, support AHCI
Power Supply : Adaptor 24, 2A
Operating Systems : Windows 7, Windows 8.1, Windows 10 IOT Enterprise, POS Ready 7

Display & Touch

Type : 15" TFT LCD, LED Backlight
Resolution : 1024 * 768
Brightness : 300 cd/m2 (typ.)
Touch Screen : Projective Capacitive Touch

Interface

Serial Port : 6 COM 1 with 5V/12V Power Output on 9 Pins, BIOS)
(COM2-3 RJ-45 , Full Signal)
(COM4 RJ-II, only TX/RX, 12V Power Output, Reserved for CDP)
(COM5 Reserved for Cash Drawer Port)
(COM6 RJ-45, only TX/RX, 5V Power Output, Reserved for MSR)
USB : 6 (Rear 2, Back 4, USB 3.0 x 2, USB 2.0 x 4)
LAN Port : 1 x Gigabit Ethernet, RJ 45
Display Port : 1 * VGA (With Power Output)
Audio : 1 x Line-out

Physical Dimension

Dimension [W*D*H] : 364 * 333 * 210 (mm)
Net Weight : 5,300g, 11.6 lbs


Environmental

Operating Condition : 0°C - 60°C at 10% to 90% Humidity
Storage Condition : -20°C - 80°C at 10% to 90% Humidity

Options & Peripherals

2nd Display : 9.7", 12.1", 15" LCD Display, 1024 x 768, Optional Touchscreen
Customer Display : VFD, 20 Columns x 2 Lines
Storage : 2.5 inch SSD 256GB, HDD 500GB, 1TB
Magnetic Stripe Reader : Comply with ISO 7811, support 1& 2 & 3 Track
Smart Card Reader : EMV Level 1, 2
Wall Mount Kit : VESA-Compatible, 75 x 75 (mm), 100 x 100 (mm)
Serial Conversion Cable : RJ-45 to D-sub 9
Wifi : Mini Pcie for Wireless LAN

Contact us

 Source and Process Solutions,
No. 1433, 2nd Floor, Pipeline Road,
West of Chord Road, 2nd Stage,
Mahalakshimpuram, Bangalore — 560086
Karnataka, India

 +91 080-41483787
+91 6366 880 942/43/44/45

 contact@sourceandprocess.in  www.sourceandprocess.in

SOURCE AND PROCESS SOLUTIONS